



Specifications Ledvance LED
Downlight Biolux HCL Zigbee Gen 2
Aluminium White 20W 2100lm 60D -
927-965 Tunable White | 175mm -
Cutout 160mm - IP20 - ZigBee

[View Product](#)

General Information

SKU	253345
EAN	4058075724600
Brand	Ledvance
Manufacturer Name	BIOLUX HCL DOWNLIGHT ZIGBEE GEN 2 DN150 S 20W TW ZB
Any Lamp all-in warranty	5 Years
Average Lifetime (h)	50000

Technical Information

Emergency Lighting	No Emergency Unit
Tiltable	No
Technology	LED Integrated
Replaces (Watt)	2x18
Wattage	20
Voltage (V)	220-240
Dimmable	Dimmable with Zigbee
Colour Code	927 Extra Warm White, 965 Daylight
Colour temperature (Kelvin)	2700 Extra Warm White, 6500 Daylight
Colour Rendering (Ra)	90-99
Colour of Light	White
Light colour options	Tunable White

Beam Angle (degree)	60
Luminous Flux (Lumen)	2100
Luminous Efficacy (lm/W)	105
Power factor	>0.90
Unified Glare Rating	< 19 - for offices and schools
Optical Cover	Opal
Finish of Reflector	Aluminium
Product Type Category	LED Downlight

Fixture Information

Mounting Method	Recessed
Cut out (mm)	160
IP-rating	IP20
Impact Protection (IK)	IK03 - 0.35 joule
Operating Temperature	-20 to +40
Housing	Aluminium
Colour of the Fixture	White
Fixture Connection	Terminal, 3-Pole (L, N, PE)

Dimensions

Height (mm)	99
Diameter (mm)	175

Why Any-lamp?

Sensor Information

 Type of sensor

Order from the **largest lighting specialist** in Europe

No Sensor



Customised quotation



Up to **7 years warranty**



Easy return process