



## Specifications Philips LED Downlight GreenSpace2 DN472B VLC-E 16.8W 2100lm 120D - 840 Cool White | 216mm - IP54 - Aluminium Reflector - Dali Dimmable

[View Product](#)

### General Information

|                          |                                   |
|--------------------------|-----------------------------------|
| SKU                      | 235993                            |
| EAN                      | 8718699384739                     |
| Brand                    | Philips                           |
| Manufacturer Name        | DN472B LED20S/840 PSED-E C PCC WH |
| Any Lamp all-in warranty | 5 Years                           |
| Average Lifetime (h)     | 50000                             |

### Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tilttable                   | No                |
| Technology                  | LED Integrated    |
| Wattage                     | 16.8              |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Dimmable          |
| Colour Code                 | 840 Cool White    |
| Colour temperature (Kelvin) | 4000 Cool White   |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |
| Light colour options        | Single Color      |
| Driver Included             | Yes               |

|                          |                          |
|--------------------------|--------------------------|
| Beam Angle (degree)      | 120                      |
| Luminous Flux (Lumen)    | 2100                     |
| Luminous Efficacy (lm/W) | 125                      |
| Power factor             | >0.90                    |
| Installation Depth (mm)  | 94                       |
| Unified Glare Rating     | < 22 - for general areas |
| Optical Cover            | PC (Polycarbonate)       |
| Finish of Reflector      | PC (Polycarbonate)       |
| Product Type Category    | LED Downlight            |

## Fixture Information

|                        |                    |
|------------------------|--------------------|
| Mounting Method        | Recessed           |
| Cut out (mm)           | 200                |
| IP-rating              | IP54               |
| Impact Protection (IK) | IK06 - 1 joule     |
| Operating Temperature  | -15 to +40         |
| Housing                | PC (Polycarbonate) |
| Colour of the Fixture  | White              |
| Colour of material     | White              |
| Series                 | GreenSpace2        |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 94  |
| Diameter (mm) | 216 |

## Why Any-lamp?



Order from the **largest lighting specialist** in Europe



**Customised** quotation

## Sensor Information



Up to **7 years warranty**



**Easy** return process

|                |           |
|----------------|-----------|
| Type of sensor | No Sensor |
|----------------|-----------|