



## Specifications Noxion LED Trunking NX-Line V2 55-70W 9900-12600lm 30D - 840 Cool White | 1500mm - 8-Pole - UGR <22

[View Product](#)

### General Information

|                          |                                                                                                     |
|--------------------------|-----------------------------------------------------------------------------------------------------|
| SKU                      | 248189                                                                                              |
| EAN                      | 8719157045995                                                                                       |
| Brand                    | Noxion                                                                                              |
| Manufacturer Name        | Noxion LED Linear Light NX-Line V2.0 Module 1500mm DIP 55/60/65/70W 4000K SP30 WH (C. L.Lens Optic) |
| Any Lamp all-in warranty | 6 Years                                                                                             |
| Average Lifetime (h)     | 50000                                                                                               |

### Technical Information

|                             |                 |
|-----------------------------|-----------------|
| Technology                  | LED Integrated  |
| Wattage                     | 55              |
| Voltage (V)                 | 220-240         |
| Dimmable                    | Not Dimmable    |
| Colour of Light             | White           |
| Colour Code                 | 840 Cool White  |
| Colour temperature (Kelvin) | 4000 Cool White |
| Colour Rendering (Ra)       | 80-89           |
| Light colour options        | Single Color    |
| Luminous Flux (Lumen)       | 9900            |
| Luminous Efficacy (lm/W)    | 180             |
| Beam Angle (degree)         | 30              |

|                       |              |
|-----------------------|--------------|
| Power factor          | >0.90        |
| Including bulb        | Yes          |
| Product Type Category | LED Trunking |

## Fixture Information

|                        |                                |
|------------------------|--------------------------------|
| Mounting Method        | Suspended                      |
| Fixture Connection     | Plug-in 230V                   |
| Optical Cover          | PMMA (Polymethyl methacrylate) |
| IP-rating              | IP20                           |
| Impact Protection (IK) | IK04 - 0.50 joule              |
| Operating Temperature  | -20 to +60                     |
| Housing                | PC (Polycarbonate), Steel      |
| Colour of the Fixture  | White                          |
| Colour of material     | White                          |
| Emergency Lighting     | No Emergency Unit              |
| Series                 | NX-Line                        |

## Dimensions

|             |      |
|-------------|------|
| Length (mm) | 1499 |
| Width (mm)  | 69.5 |
| Height (mm) | 39.4 |

## Sensor Information

## Why Any-lamp?

|                                                                                                                                                                                                                                                                   |           |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|
| Type of sensor                                                                                                                                                                                                                                                    | No Sensor |
|  Order from the <b>largest lighting specialist</b> in Europe  <b>Customised</b> quotation |           |
|  Up to <b>7 years warranty</b>  <b>Easy</b> return process                                  |           |