



Specifications Multipack 15x Noxion LED Downlight Apollo 20W 2300lm 60D - 830 Warm White | 220mm - Cutout 200mm - Alu Reflector - UGR <19

[View Product](#)

General Information

|                          |                                                                                                     |
|--------------------------|-----------------------------------------------------------------------------------------------------|
| SKU                      | 248649                                                                                              |
| EAN                      | 8719157048088                                                                                       |
| Brand                    | Noxion                                                                                              |
| Manufacturer Name        | Multipack 15x Noxion LED Downlight Apollo 20W 2300LM 3000K Cutout Ø200mm Frame Ø220mm Alu Reflector |
| Any Lamp all-in warranty | 6 Years                                                                                             |
| Average Lifetime (h)     | 60000                                                                                               |

Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tiltable                    | No                |
| Technology                  | LED Integrated    |
| Replaces (Watt)             | 45                |
| Wattage                     | 20                |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Not Dimmable      |
| Colour Code                 | 830 Warm White    |
| Colour temperature (Kelvin) | 3000 Warm White   |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |

|                          |                                |
|--------------------------|--------------------------------|
| Light colour options     | Single Color                   |
| Including bulb           | Yes                            |
| Beam Angle (degree)      | 60                             |
| Luminous Flux (Lumen)    | 2500                           |
| Luminous Efficacy (lm/W) | 125                            |
| Power factor             | >0.90                          |
| Unified Glare Rating     | < 19 - for offices and schools |
| Optical Cover            | PC (Polycarbonate)             |
| Finish of Reflector      | Aluminium                      |
| Product Type Category    | LED Downlight                  |

## Fixture Information

|                        |                   |
|------------------------|-------------------|
| Mounting Method        | Recessed          |
| Cut out (mm)           | 200               |
| IP-rating              | IP20              |
| Impact Protection (IK) | IK03 - 0.35 joule |
| Operating Temperature  | -20 to +40        |
| Housing                | Aluminium         |
| Colour of the Fixture  | White             |
| Colour of material     | White             |
| Series                 | Apollo            |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 141 |
| Diameter (mm) | 220 |

## Sensor Information

Type of sensor

No Sensor

### Why Any-lamp?



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process

