



Specifications Multipack 4x Ledvance  
LED Downlight Alu DN150 14W 1190lm  
100D - 830 Warm White | 160mm -  
IP44

[View Product](#)

## General Information

|                          |                                                  |
|--------------------------|--------------------------------------------------|
| SKU                      | 253043                                           |
| EAN                      | 8719157059398                                    |
| Brand                    | Ledvance                                         |
| Manufacturer Name        | Multipack 4x DL ALU DN150 14W/3000K WT IP44 LEDV |
| Any Lamp all-in warranty | 5 Years                                          |
| Average Lifetime (h)     | 50000                                            |

## Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tilttable                   | No                |
| Technology                  | LED Integrated    |
| Replaces (Watt)             | 1x26              |
| Wattage                     | 14                |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Not Dimmable      |
| Colour Code                 | 830 Warm White    |
| Colour temperature (Kelvin) | 3000 Warm White   |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |
| Light colour options        | Single Color      |

|                          |                                       |
|--------------------------|---------------------------------------|
| Beam Angle (degree)      | 100                                   |
| Luminous Flux (Lumen)    | 1190                                  |
| Luminous Efficacy (lm/W) | 85                                    |
| Power factor             | >0.90                                 |
| Unified Glare Rating     | < 28 - for hallways and storage rooms |
| Optical Cover            | PMMA (Polymethyl methacrylate)        |
| Product Type Category    | LED Downlight                         |

## Fixture Information

|                        |                               |
|------------------------|-------------------------------|
| Mounting Method        | Recessed                      |
| Cut out (mm)           | 150                           |
| IP-rating              | IP44                          |
| Impact Protection (IK) | IK02 - 0.20 joule             |
| Operating Temperature  | -20 to +45                    |
| Housing                | Aluminium                     |
| Colour of the Fixture  | White                         |
| Fixture Connection     | PI [Push-in connector 2-pole] |
| Series                 | DOWNLIGHT ALU                 |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 52  |
| Diameter (mm) | 160 |

## Why Any-lamp?

## Sensor Information


 Order from the **largest lighting specialist** in Europe


**Customised** quotation

Type of sensor
 


 No Sensor


 Up to **7 years warranty**


**Easy** return process